

#### SAFETY DATA SHEET

# Liquid Moisture Barrier

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name

Liquid Moisture Barrier

Unique formula identifier (UFI)

9F30-N0V2-W00U-9G51

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

▼ Relevant identified uses of the substance or mixture

Moisture barrier for concrete.

Restricted to professional users.

**▼** Uses advised against

None known.

# 1.3. Details of the supplier of the safety data sheet

# Company and address

# Junckers Industrier A/S

Vaerftsvej 4

4600 Koege

Denmark

Tel. +45 70 80 30 00

#### E-mai

productsafety@junckers.dk

Revision

07/05/2024

SDS Version

2.0

# Date of previous version

17/04/2023 (1.0)

### 1.4. Emergency telephone number

The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am-10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

### SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

#### 2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Irrit. 2; H319, Causes serious eye irritation.

Acute Tox. 4; H332, Harmful if inhaled.

Resp. Sens. 1; H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT SE 3; H335, May cause respiratory irritation.

Carc. 2; H351, Suspected of causing cancer.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

#### 2.2. Label elements

# Hazard pictogram(s)





### Signal word

Danger

### Hazard statement(s)

Causes skin irritation. (H315)

May cause an allergic skin reaction. (H317)

Causes serious eye irritation. (H319)

Harmful if inhaled. (H332)

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (H334)

May cause respiratory irritation. (H335) Suspected of causing cancer. (H351)

May cause damage to organs through prolonged or repeated exposure. (H373)

#### Precautionary statement(s)

General

-

#### Prevention

Do not breathe vapour. (P260)

Wear eye protection/protective gloves/protective clothing. (P280)

[In case of inadequate ventilation] wear respiratory protection. (P284)

#### Response

IF ON SKIN: Wash with plenty of water and soap. (P302+P352)

IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304+P340)

If experiencing respiratory symptoms: Call a POISON CENTER/doctor (P342+P311)

# Storage

\_

# Disposal

\_

### Hazardous substances

4,4'-Methylenediphenyl diisocyanate

2,4'-Methylenediphenyl diisocyanate

Diphenylmethane diisocyanate, isomers and homologues

2,2'-Methylenediphenyl diisocyanate

# Additional labelling

As from 24 August 2023 adequate training is required before industrial or professional use.

UFI: 9F30-N0V2-W00U-9G51

# 2.3. Other hazards

# ▼Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

# SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

# 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
4,4'-Methylenediphenyl diisocyanate	CAS No.: 101-68-8 EC No.: 202-966-0 REACH: Index No.: 615-005-00-9	25-40%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Acute Tox. 4, H332 Resp. Sens. 1, H334 (SCL: 0.10 %) STOT SE 3, H335 (SCL: 5.00 %) Carc. 2, H351 STOT RE 2, H373 (Inhalation)	[3]
Prepolymer based on aromatic polyisocyanate	CAS No.: 67815-87-6 EC No.: 642-899-8 REACH:	25-40%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	



	Index No.:		Resp. Sens. 1, H334 STOT SE 3, H335 STOT RE 2, H373	
2,4'-Methylenediphenyl diisocyanate	CAS No.: 5873-54-1 EC No.: 227-534-9 REACH: 01-2119480143-45 Index No.: 615-005-00-9	15-25%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Acute Tox. 4, H332 Resp. Sens. 1, H334 (SCL: 0.10 %) STOT SE 3, H335 (SCL: 5.00 %) Carc. 2, H351 STOT RE 2, H373 (Inhalation)	[3]
Diphenylmethane diisocyanate, isomers and homologues	CAS No.: 9016-87-9 EC No.: 618-498-9 REACH: Index No.:	3-5%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 (Inhalation)	
2,2'-Methylenediphenyl diisocyanate	CAS No.: 2536-05-2 EC No.: 219-799-4 REACH: 01-2119927323-43 Index No.: 615-005-00-9	3-5%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Acute Tox. 4, H332 Resp. Sens. 1, H334 (SCL: 0.10 %) STOT SE 3, H335 (SCL: 5.00 %) Carc. 2, H351 STOT RE 2, H373 (Inhalation)	[3]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

# Other information

[3] According to REACH, Annex XVII, the substance is subject to restrictions.

# SECTION 4: First aid measures

# 4.1. Description of first aid measures

# **General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.

### **▼** Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

# Ingestion



If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Burns

Not applicable.

# 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO<sub>x</sub>)

Carbon oxides (CO / CO2)

# 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice.

### SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

# 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, soil, vermiculite or similar to collect liquid material. Subsequently, place in a suitable waste container.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

#### 7.1. ▼ Precautions for safe handling

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.



### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Recommended storage material

Always store in containers of the same material as the original container.

# Storage temperature

Store in cool, dry conditions in well sealed receptacles.

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

# SECTION 8: Exposure controls/personal protection

### 8.1. ▼ Control parameters

4,4'-Methylenediphenyl diisocyanate

Long term exposure limit (8 hours) (ppm): 0.005

Annotations:

Sen = Chemical agent which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis.

### 2,4'-Methylenediphenyl diisocyanate

Long term exposure limit (8 hours) (mg/m³): 0.02

Short term exposure limit (15 minutes) (mg/m³): 0.07

Annotations:

Sen = Chemical agent which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis.

#### 2,2'-Methylenediphenyl diisocyanate

Long term exposure limit (8 hours) (mg/m³): 0.02

Short term exposure limit (15 minutes) (mg/m³): 0.07

Annotations:

Sen = Chemical agent which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis.

2024 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2021) and the Safety, Health and Welfare at Work (Carcinogens, Mutagens and Reprotoxic Substances) Regulations (2024).

#### **DNEL**

# 2,2'-Methylenediphenyl diisocyanate

Route of exposure:	DNEL:
Inhalation	0,025 mg/m³
Inhalation	0,05 mg/m³
Inhalation	0,05 mg/m³
Inhalation	0,1 mg/m³
Route of exposure:	DNEL:
Inhalation	0,025 mg/m³
Inhalation	0,05 mg/m³
Inhalation	0,05 m/m³
Inhalation	0,1 mg/m³
Route of exposure:	DNEL:
Inhalation	0,025 mg/m <sup>3</sup>
	Inhalation Inhalation Inhalation Inhalation  Route of exposure: Inhalation Inhalation Inhalation Inhalation Inhalation Inhalation Route of exposure:

Inhalation

Long term - Local effects - Workers

0,05 mg/m<sup>3</sup>



Short term – Local effects - General population	Inhalation	0,05 mg/m³
Short term – Local effects - Workers	Inhalation	0,1 mg/m³

#### **PNEC**

#### 2,2'-Methylenediphenyl diisocyanate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1 mg/l
Intermittent release (freshwater)		10 mg/l
Marine water		0,1 mg/l
Sewage treatment plant		1 mg/l
Soil		1 mg/kg dw

### 2,4'-Methylenediphenyl diisocyanate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1 mg/l
Intermittent release (freshwater)		10 mg/l
Marine water		0,1 mg/l
Sewage treatment plant		1 mg/l
Soil		1 mg/kg dw

# 4,4'-Methylenediphenyl diisocyanate

i, i weerly eneapherry ansocyanace		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1 mg/l
Intermittent release (freshwater)		10 mg/l
Marine water		0,1 mg/l
Sewage treatment plant		1 mg/l
Soil		1 mg/kg dw

### 8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### ▼ Appropriate technical measures

Do not recirculate outlet air that contain the substances.

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

# Hygiene measures

Take off contaminated clothing and wash it before reuse.

# Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

# Individual protection measures, such as personal protective equipment

#### Generally

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (e.g. type A1 according to standard EN 14387) is used.

Use only CE marked protective equipment.

# **Respiratory Equipment**



Work situation	Туре	Class	Colour	Standards	
In case of insufficient ventilation	Gas filter A	2 (medium capacity)	Brown	EN14387	

### Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	R
The second second			

## Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,4	> 480	EN374-2, EN374-3, EN388	



### Eye

shields

e protection		
Туре	Standards	
Safety glasses	s with side EN166	



# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

# Physical state

Liquid

Colour

**Amber** 

Odour / Odour threshold

Faint

Testing not relevant or not possible due to the nature of the product.

Density (g/cm<sup>3</sup>)

1,18

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

## Phase changes

# Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.



### Data on fire and explosion hazards

#### Flash point (°C)

110

#### Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

# Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

### Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

#### Solubility

### Solubility in water

Testing not relevant or not possible due to the nature of the product.

# n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

## Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

#### 9.2. Other information

### Other physical and chemical parameters

No data available.

#### Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

# SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

# 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

# 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Acute toxicity

Harmful if inhaled.

# Skin corrosion/irritation

Causes skin irritation.

# Serious eye damage/irritation

Causes serious eye irritation.

# Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# Skin sensitisation

May cause an allergic skin reaction.

## Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Suspected of causing cancer.

# Reproductive toxicity

Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause respiratory irritation.



#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

#### Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

#### Other information

4,4'-Methylenediphenyl diisocyanate has been classified by IARC as a group 3 carcinogen.

Diphenylmethane diisocyanate, isomers and homologues has been classified by IARC as a group 3 carcinogen.

# SECTION 12: Ecological information

#### 12.1. Toxicity

No data available.

# 12.2. ▼ Persistence and degradability

Based on available data, the classification criteria are not met.

### 12.3. ▼ Bioaccumulative potential

Based on available data, the classification criteria are not met.

### 12.4. Mobility in soil

No data available.

### 12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

# 12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

## 12.7. Other adverse effects

None known.

### **SECTION 13: Disposal considerations**

# 13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

HP 7 - Carcinogenic

HP 13 - Sensitising

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

### **▼** EWC code

08 05 01\* Waste isocyanates

# Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

# SECTION 14: Transport information

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 14.5 Other PG* Env** information
ADR		-	
IMDG	-	-	



	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IATA	-	-	-	-	-

<sup>\*</sup> Packing group

#### \*\* Environmental hazards

### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

#### SEVESO - Categories / dangerous substances

Not applicable.

#### ▼ REACH, Annex XVII

4,4'-Methylenediphenyl diisocyanate is subject to REACH restrictions, REACH annex XVII (entry 56; 74).

2,4'-Methylenediphenyl diisocyanate is subject to REACH restrictions, REACH annex XVII (entry 56; 74).

2,2'-Methylenediphenyl diisocyanate is subject to REACH restrictions, REACH annex XVII (entry 56; 74).

#### **▼** Additional information

EMICODE: EC 1 PLUS - very low emission PLUS.

# Sources

Protection of Young Persons (Employment) Act, 1996

Maternity Protection Act 1994 (34/1994) with later amendments.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

No

#### SECTION 16: Other information

# Full text of H-phrases as mentioned in section 3

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335, May cause respiratory irritation.

H351, Suspected of causing cancer.

H373, May cause damage to organs through prolonged or repeated exposure. (Inhalation)

H373, May cause damage to organs through prolonged or repeated exposure.

# Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor



CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH = CLP-specific hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of classification and labelling of chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = Logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = Specific Concentration Limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time Weighted Average

**UN = United Nations** 

UVCB = Substances of Unknown or Variable composition, Complex reaction products or Biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and very Bioaccumulative

### Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

# ▼ The safety data sheet is validated by

ULS

# **▼** Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en